


SOD-523 SURFACE MOUNT ZENER DIODES

FEATURES

- The plastic package carries Underwrites Laboratory Flammability Classification 94V-0
- Construction utilizes void-free molded plastic technique
- High reliability
- High temperature soldering guaranteed: 260 °C/10 seconds at terminals
- Component in accordance to RoHS 2015/863 and WEEE 2012/19/EU

MECHANICAL DATA

- Case style: SOD-523 molded plastic
- Mounting position: Any



MAXIMUM RATINGS AND CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified

Characteristic	Symbol	Value	Unit
Forward Voltage @ $I_F=10\text{mA}$	V_F	0.9	V
Power Dissipation	PD	150	mW
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	833	°C/W
Junction Temperature	T_J	150	°C
Storage Temperature	T_{stg}	-55~+150	°C


Type Number	Type Code	Zener Voltage Range (Note 2)				Maximum Zener Impedance (Note 3)			Maximum Reverse Current		Typical temperature coefficient @ I_{ZT} mV/°C	
		$V_Z @ I_{ZT}$			I_{ZT}	$Z_{ZT} @ I_{ZT}$	$Z_{ZK} @ I_{ZK}$		I_R	V_R		
		Nom(V)	Min(V)	Max(V)	(mA)	(Ω)	(mA)		(μA)	(V)	Min	Max
BZX584C2V4	Z11	2.4	2.20	2.60	5	100	600	1.0	50	1.0	-3.5	0
BZX584C2V7	Z12	2.7	2.5	2.9	5	100	600	1.0	20	1.0	-3.5	0
BZX584C3V0	Z13	3.0	2.8	3.2	5	95	600	1.0	10	1.0	-3.5	0
BZX584C3V3	Z14	3.3	3.1	3.5	5	95	600	1.0	5	1.0	-3.5	0
BZX584C3V6	Z15	3.6	3.4	3.8	5	90	600	1.0	5	1.0	-3.5	0
BZX584C3V9	Z16	3.9	3.7	4.1	5	90	600	1.0	3	1.0	-3.5	0
BZX584C4V3	Z17	4.3	4.0	4.6	5	90	600	1.0	3	1.0	-3.5	0
BZX584C4V7	Z1	4.7	4.4	5.0	5	80	500	1.0	3	2.0	-3.5	0.2
BZX584C5V1	Z2	5.1	4.8	5.4	5	60	480	1.0	2	2.0	-2.7	1.2

Electrical Specification (T_A=25°C unless otherwise specified)


Type Number	Type Code	Zener Voltage Range (Note 2)				Maximum Zener Impedance (Note 3)			Maximum Reverse Current		Typical temperature coefficient @ I _{ZT} mV/°C	
		V _Z @I _{ZT}			I _{ZT}	Z _{ZT} @I _{ZT}	Z _{ZK} @I _{ZK}		I _R	V _R		
		Nom(V)	Min(V)	Max(V)	(mA)	(Ω)	(mA)		(μA)	(V)	Min	Max
BZX584C5V6	Z3	5.6	5.2	6.0	5	40	400		1	2.0	-2.0	2.5
BZX584C6V2	Z4	6.2	5.8	6.6	5	10	150		3	4.0	0.4	3.7
BZX584C6V8	Z5	6.8	6.4	7.2	5	15	80		2	4.0	1.2	4.5
BZX584C7V5	Z6	7.5	7.0	7.9	5	15	80		1	5.0	2.5	5.3
BZX584C8V2	Z7	8.2	7.7	8.7	5	15	80		0.7	5.0	3.2	6.2
BZX584C9V1	Z8	9.1	8.5	9.6	5	15	100		0.5	6.0	3.8	7.0
BZX584C10	Z9	10	9.4	10.6	5	20	150		0.2	7.0	4.5	8.0
BZX584C11	Y1	11	10.4	11.6	5	20	150		0.1	8.0	5.4	9.0
BZX584C12	Y2	12	11.4	12.7	5	25	150		0.1	8.0	6.0	10.0
BZX584C13	Y3	13	12.4	14.1	5	30	170		0.1	8.0	7.0	11.0
BZX584C15	Y4	15	13.8	15.6	5	30	200		0.1	10.5	9.2	13.0
BZX584C16	Y5	16	15.3	17.1	5	40	200		0.1	11.2	10.4	14.0
BZX584C18	Y6	18	16.8	19.1	5	45	225		0.1	12.6	12.4	16.0
BZX584C20	Y7	20	18.8	21.2	5	55	225		0.1	14.0	14.4	18.0
BZX584C22	Y8	22	20.8	23.3	5	55	250		0.1	15.4	16.4	20.0
BZX584C24	Y9	24	22.8	25.6	5	70	250		0.1	16.8	18.4	22.0
BZX584C27	Y10	27	25.1	28.9	2	80	300		0.1	18.9	21.4	25.3
BZX584C30	Y11	30	28.0	32.0	2	80	300		0.1	21.0	24.4	29.4
BZX584C33	Y12	33	31.0	35.0	2	80	325		0.1	23.1	27.4	33.4
BZX584C36	Y13	36	34.0	38.0	2	90	350		0.1	25.2	30.4	37.4
BZX584C39	Y14	39	37.0	41.0	2	130	350		0.1	27.3	33.4	41.2
BZX584C43	Y15	43	40.0	46.0	2	100	700		0.1	32	10	12

RATINGS AND CHARACTERISTIC CURVES


Zener Characteristics (V_Z Up to 10 V)




Zener Characteristics (11 V to 43 V)




Temperature Coefficients



Typical Leakage Current



Typical Capacitance



Effect of Zener Voltage on Zener Impedance

